



RAVENOL Automatik-Getriebeöl ATF 5/4 HP Fluid

ATF Professional Line

RAVENOL ATF 5/4 HP Fluid is a fully synthetic ATF produced on the basis of PAO with a special additivation and inhibition which guarantees a perfect function of the automatic transmission.

RAVENOL ATF 5/4 HP Fluid is a automatic transmission oil ATF of the latest generation for all 4- and 5 stroke automatic transmissions of ZF. It guarantees in any mode for maximum wear protection. RAVENOL ATF 5/4 HP Fluid has a neutral brown color.

Application Notes

RAVENOL ATF 5/4 HP Fluid is suitable for use in automatic transmission of ZF Serie 4 HP (4HP20, 4HP22, 4HP24) und 5HP (5HP18, 5HP19, 5HP24, 5HP30). Maintenance-filling under normal operating conditions.

Quality Classifications

Practice and tested in aggregates with filling

Alfa Romeo 20HP 14891900, ATF LT 71141, ATF LA 2634, BMW 8322 9407765, BMW 8322 9407807, Citroën/Peugeot AL4 PR 9736.22, Jaguar JLM 20237, Land Rover STC4863, Mercedes A 0019892203, Porsche 999.917.547.00, Renault DP0, VW/Audi G052162 A1/ A2/ A6, VW TL 52 162, ZF S671 090 170

Characteristic

RAVENOL ATF 5/4 HP Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity.

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	847	EN ISO 12185
Pourpoint	°C	-42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

16.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41