



## RAVENOL DOT 5.1

RAVENOL DOT 5.1 is a brake fluid for the use in all vehicles with optimum ABS characteristics. There is a chemical stability and it is provided with additives which save the best lubrication efficiency.

Because of the special formulation of RAVENOL DOT 5.1 the international specifications SAE J1704, ISO 4925 and the safety regulations FMVSS 116 DOT 5.1 from the United States of America are exceeded.

### Application Notes

RAVENOL DOT 5.1 can be used in all vehicles for which the DOT 5.1 specification for brake fluids is required. It is suitable for all hydraulic brake systems with synthetic fluids.

RAVENOL DOT 5.1 is miscible with all known brake fluids of the same specification.

### Quality Classifications

#### **Specifications**

SAE J1704, ISO 4925 Class 5-1, FMVSS 116 DOT 5.1

#### **Characteristic**

RAVENOL DOT 5.1 offers:

- optimum ABS characteristics
- chemical stability
- best lubrication efficiency
- neutral behaviour against brake parts
- low viscosity at low temperatures
- miscible with all brake fluids of the same specification

Characteristics	Unit	Data	Audit
Boiling point	°C	min. 260	SAE J1704
wet boiling point	°C	min. 180	SAE J1704
Viscosity at -40°C	mPa*s	max. 900	SAE J1704

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

21.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41