



RAVENOL RUP Racing Ultra Performance SAE 5W-40

RAVENOL RUP Racing Ultra Performance SAE 5W-40 is a modern, fully synthetic, fuel-saving, low friction multigrade engine oil. Due to its low sulphated ash content RAVENOL RUP Racing Ultra Performance SAE 5W-40 therefore contributes to reducing emissions and protecting the environment. It is extremely well-suited to modern petrol engines for car racing, even when subject to the highest levels of strain.

As a result of its special additives using tungsten, RAVENOL RUP Racing Ultra Performance SAE 5W-40 is also suitable for extremely sporty driving styles. It utilizes the positive properties of tungsten to smooth the surface structure of the motor, reducing friction and wear, and significantly improving mechanical efficiency. It provides a safe layer of lubrication, even at very high operating temperatures. Extensive protection against corrosion (oxidation) and foaming.

Application Notes

RAVENOL RUP Racing Ultra Performance SAE 5W-40 can be used as special oil for car race even under most difficult conditions.

Specifications

API SN

Approvals

Renault RN0700/RN0710, VW 502 00, VW 505 00, VW 505 01, GM Dexos 2 (Lizenz Nr. D20583HI081)

Practice and tested in aggregates with filling

MB 229.51, MB 226.5, BMW Longlife-04, Porsche A40, Ford WSS-M2C917-A, Race Partnerships: Nürburgring Tested, Hockenheim Premium Partner, Recommendation of Ralf Schumacher

Characteristic

RAVENOL RUP Racing Ultra Performance SAE 5W-40 offers:

- Ultra-modern fully synthetic engine oil for car race with special tungsten addition
- Fuel saving regarding partial load operation and full power operation
- Very low evaporation tendency
- Very stable and excellent viscosity behaviour
- Very good cold start characteristics
- Safe lubricating layer at very high operating temperatures
- Very good detergent and dispersant characteristics
- Good protection against corrosion and foam formation

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	846	DIN 51757
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	14,3	DIN 51562
Viscosity at 40°C	mm ² /s	87,5	DIN 51562
Viscosity index VI		169	DIN ISO 2909
HTHS at 150°C	mPa*s	3,9	CEC-L-36-A-90
CCS Viscosity at -30°C	mPa*s	4510	ASTM D5293
Low Temp. Pumping viscosity (MRV)	mPa*s	21.300	ASTM D4684
Pourpoint	°C	-51	DIN ISO 3016
Noack Volatility	%	6,0	ASTM D5800/b
Flash point (COC)	°C	244	DIN ISO 2592
TBN	mg KOH/g	8,3	ASTM D2896
Sulphated ash	%wt.	0,8	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

29.11.2017