



RAVENOL SCOOTER 2-Takt Fullsynth.

RAVENOL SCOOTER 2-Takt Fullsynth. is high quality fully synthetic two-stroke engine oil.

RAVENOL SCOOTER 2-Takt Fullsynth. is based on Polyolester with special esters and Polyisobutylene (PIB) for optimum protection against wear and prevent corrosion, deposits and auto-ignitions, even with heavy loads.

RAVENOL SCOOTER 2-Takt Fullsynth. is optimized for air- and watercooled two stroke engines in Scooters.

Application Notes

RAVENOL SCOOTER 2-Takt Fullsynth. can generally be mixed with regular petrol 1:100.

RAVENOL SCOOTER 2-Takt Fullsynth. is best choice for air- and watercooled two stroke engines in Scooters.

RAVENOL SCOOTER 2-Takt Fullsynth. is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

RAVENOL SCOOTER 2-Takt Fullsynth. is also suitable for the lubrication of two stroke scooters with water cooling. Suitable for separate lubrication systems and self-mixing systems.

Quality Classifications

RAVENOL SCOOTER 2-Takt Fullsynth. corresponds to and fulfils following specification:

Specifications

API TD, ISO-L-EGD

Approvals

JASO 049RAV153

Practice and tested in aggregates with filling

Aprilia, Honda, Kymco, Peugeot, Piaggio, Suzuki, Vespa, Yamaha

Characteristic

RAVENOL SCOOTER 2-Takt Fullsynth. offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean sparkplugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion

Characteristics	Unit	Data	Audit
Colour		red	visual
Density at 15°C	kg/m ³	0,872	EN ISO 12185
Viscosity at 40°C	mm ² /s	48,0	DIN 51 562
Viscosity at 100°C	mm ² /s	8,0	DIN 51 562
Viscosity index VI		138	DIN ISO 2909
Pourpoint	°C	- 21	DIN ISO 3016
Sulphated ash	%wt.	<0,04	DIN 51 575
TBN	mg KOH/g	2,4	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

15.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41